

Contact insert - HC-D 8-EBUC - 1775745


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON female insert, D8 series, 8-pos., crimp connection, with IP65 sealing screw



Key commercial data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 017918 038304
Weight per Piece (excluding packing)	12.76 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Note	For HC-D8 housing, crimp contacts CK1,6-ED (crimp contacts not included in scope of supply)
Connection method	Crimp connection
Pollution degree	3
Surge voltage category	III
Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Number of positions	8
Insertion/withdrawal cycles	≥ 500
Type	D8
Connection in acc. with standard	IEC / EN
Conductor cross section	0.14 mm ² ... 2.5 mm ²
Connection cross section AWG	26 ... 14

Contact insert - HC-D 8-EBUC - 1775745

Technical data

General

Stripping length of the individual wire	8 mm
	6 mm (for cross section 2.5 mm ²)
Assembly instructions	Connectors may be operated only when there is no load/voltage.
Connection	The inserts may only be used in plastic housings at voltages >42 V, since it is not possible to connect the protective conductor and the housing with each other.

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
---------------------------------	--

Material data

Inflammability class according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	50 V
Rated surge voltage	0.8 kV
Rated current	10 A

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440205

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522

Contact insert - HC-D 8-EBUC - 1775745

Classifications

UNSPSC

UNSPSC 13.2	39121522
-------------	----------

Approvals

Approvals

Approvals

CSA / UL Recognized / EAC

Ex Approvals

Approvals submitted

Approval details

CSA	
mm ² /AWG/kcmil	22-16
Nominal current I _N	10 A
Nominal voltage U _N	300 V

UL Recognized

EAC

Accessories

Accessories

Coding element

Dummy socket - CK1,6-ED-BB - 1645888




Dummy socket for contact carrier with turned CK 1,6-ED.. female contacts

Contact insert - HC-D 8-EBUC - 1775745

Accessories


Drawings

Schematic diagram




Connector pin assignment, connection side

Diagram



Derating diagram: HC-D...C series

Dimensioned drawing



Female insert (turned contacts)