## 100C43VA10

Allen-Bradley 100C Contactor 22kW 3Pole 230 to 240VAC Coil 1NO Contact Auxiliary





Component type	Power contactor, AC switching	
Range	100C	
Model	N/A	
Alternative	100C43T10	

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

	Number of normally open contacts as main contact	3.0
ELECTRICAL	Number of normally closed contacts as main contact	0.0
	Rated operation current le at AC-3, 400 V	43.0 A
	Rated operation power at AC-3, 400 V	22.0 kW
	Rated operation current le at AC-1, 400 V	85.0 A
	Max. rated operation voltage Ue AC	690.0 V
	Voltage type for actuating	AC
	Rated control supply voltage Us at AC 50HZ	230 - 240 V
	Number of auxiliary contacts as normally open contact	1.0
	Number of auxiliary contacts as normally closed contact	0.0
	Rated operation current le at AC-3, 690 V	25.0 A
	Rated operation power at AC-3, 690 V	22.0 kW
	Rated operation power at AC-4, 400 V	6.3 kW
	Power consumption, AC coil pickup	135.0 VA
	Power consumption, AC coil hold-in	13.3 VA
	Type of electrical connection of main circuit	Screw connection
	Rated operation current le at AC-4, 400 V	14.0 A
CONSTRUCTION	Degree of protection (IP)	IP20
	Mounting method	DIN-rail/screw
DIMENSIONS	Height	81.0 mm
	Width	63.0 mm
	Depth	107.0 mm
	Weight	0.53 kg



## **DIMENSIONAL DIAGRAM**

