



Representative Photo Only  
(actual product may vary based on configuration selections)

Contactor 3 pole 140A 90kW 1N/O 1N/C auxiliary 110...130V  
50/60Hz AC Coil with electronic interface

- Averages 50% smaller dimensions than others in its class, for minimal panel space
- Features enclosed and interlocked arc chambers for safety
- Wide range of accessories to suit application requirements

## SPECIFICATIONS

Product Series	100-D
Component Type Motor Control and Drives	Standard Contactor
Ie, Rated Operational Current, AC-1, 415V, 40°C	250 A@415V,40°C
kW Rating, AC-3, 415V, 60°C	90 kW @415V, 60°C
Ie, Rated Operational Current, AC-3, 415V, 60°C	155 A@415V,60°C
Ie, Rated Operational Current, AC-3, 690V, 60°C	115 A@690V,60°C
kW Rating, AC-3, 1kV, 60°C	75 kW @1kV, 60°C
Ie, Rated Operational Current, AC-3, 1000V, 60°C	55 A@1000V,60°C
Number of Poles	3
Coil Type	Electronic w/ EI type
Rated Frequency	50 / 60 Hz
Un, Coil Voltage, AC @50Hz, Min	110 V AC min @50Hz
Un, Coil Voltage, AC @50Hz, Max	130 V AC max @50Hz
Un, Coil Voltage, AC @60Hz, Min	110 V AC min @60Hz
Un, Coil Voltage, AC @60Hz, Max	130 V AC max @60Hz
IP Rating	IP00

## REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-