

100FA40

Allen-Bradley 100C Auxiliary Contact with 4NO Contacts Front Mount



| | |
|----------------|-------------------------|
| Component type | Auxiliary contact block |
| Range | 100C |
| Model | N/A |
| Product status | Existing |

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

ELECTRICAL

| | |
|---|--------|
| Number of contacts as normally open contact | 4 |
| Rated insulation voltage Ui | 690 V |
| Rated operation current Ie at AC-15, 24 V | 6 A |
| Rated operation current Ie at AC-15, 120 V | 6 A |
| Rated operation current Ie at AC-15, 240 V | 5 A |
| Rated operation current Ie at AC-15, 400 V | 3 A |
| Rated operation current Ie at DC-12, 24 V | 12 A |
| Rated operation current Ie at DC-12, 110 V | 3.5 A |
| Rated operation current Ie at DC-12, 220 V | 0.55 A |
| Rated operation current Ie at DC-13, 24 V | 5 A |
| Rated operation current Ie at DC-13, 110 V | 1.2 A |
| Rated operation current Ie at DC-13, 220 V | 0.6 A |
| Min. contact rating current | 5 mA |
| Min. contact rating voltage | 17 V |
| Rated operation current Ie at AC-15, 230 V | 5.5 A |

CONSTRUCTION

| | |
|-----------------|--------------|
| Mounting method | Top mounting |
|-----------------|--------------|