

# 100FB11

Allen-Bradley 100C Auxiliary Contact with 1NO Contact and 1NC Contact Front Mount



CONTACTORS



Allen-Bradley



Component type	Auxiliary contact block
Range	100C
Model	N/A
Product status	Existing

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

## ELECTRICAL

Number of contacts as normally open contact	1
Number of contacts as normally closed contact	1
Rated insulation voltage Ui	690 V
Rated operation current Ie at AC-15, 24 V	6 A
Rated operation current Ie at AC-15, 120 V	6 A
Rated operation current Ie at AC-15, 240 V	5 A
Rated operation current Ie at AC-15, 400 V	3 A
Rated operation current Ie at DC-12, 24 V	12 A
Rated operation current Ie at DC-12, 110 V	3.5 A
Rated operation current Ie at DC-12, 220 V	0.55 A
Rated operation current Ie at DC-13, 24 V	5 A
Rated operation current Ie at DC-13, 110 V	1.2 A
Rated operation current Ie at DC-13, 220 V	0.6 A
Min. contact rating current	5 mA
Min. contact rating voltage	17 V
Rated operation current Ie at AC-15, 230 V	5.5 A

## CONSTRUCTION

Mounting method	Top mounting
-----------------	--------------