


Technical Data

Target size		static: 10 mm dynamic: 30 mm (at $v = 1.6$ m/s of the obstacle)
Angle of divergence		$< 5^\circ$
Functional safety related parameters		
Safety Integrity Level (SIL)		SIL 3
Performance level (PL)		PL e
Category		Cat. 4
Mission Time (T_M)		20 a
PFH_d		4.4 E-10
Type		4
Indicators/operating means		
Function indicator		LED yellow/green in receiver: off: Interruption yellow: transmission green: reception with sufficient stability control
Pre-fault indicator		LED functional display yellow
Electrical specifications		
Operating voltage	U_B	Power supply via control unit
Conformity		
Functional safety		ISO 13849-1
Product standard		EN 61496-1 ; IEC 61496-2
Approvals and certificates		
CE conformity		CE
CCC approval		CCC approval / marking not required for products rated ≤ 36 V
Approvals		TÜV
Ambient conditions		
Ambient temperature		-20 ... 60 °C (-4 ... 140 °F)
Storage temperature		-20 ... 70 °C (-4 ... 158 °F)
Relative humidity		max. 95 %, not condensing
Mechanical specifications		
Degree of protection		IP65
Connection		2 m, 0.25 mm ² fixed cable
Material		
Housing		diecast aluminum, RLA 1021 (yellow) painted
Optical face		glass pane
Mass		per 100 g

Connection

Design with fixed cable


Receiver:



Emitter:

Design with fixed cable

Receiver:




Emitter:

Characteristic Curve


Characteristic response curve


SLA40



Relative received light strength

SLA40





Accessories

	OMH-40	Mounting bracket
	SLA-1-M	Deviation mirror

System accessories

Control units

SB4 (SafeBox)

Cable sockets (only option /92)

straight: V1-G-2M-PVC

V1-G-5M-PVC

V1-G-10M-PVC

angled: V1-W-2M-PVC

V1-W-5M-PVC

V1-W-10M-PVC

Mounting aids

OMH-40

Further accessories

Redirection mirror

SLA-1-M