700HA33A2

Allen-Bradley 700-HA General Purpose Tube Base Relay 10A 3 Changeover 3PDT 240V AC Coil





Component type	Switching relay
Range	Panel Mount and Power Relays
Model	N/A
Product status	Existing

	Nominal current	10.0 A
CONSTRUCTION	Nominal voltage AC	250.0 V
	Number of contacts as change-over contact	3.0
	Rated switching power at AC-1	2500.0 VA
	Rated switching power at AC-15, 230V	500.0 VA
	Breaking capacity at DC-1, 30V	10.0 A
	Voltage type for actuating	AC
	Control supply voltage Us at AC 50HZ	240.0 V
	Control supply voltage Us at AC 60HZ	240.0 V
	Type of electric connection	Plug-in connection
	Electrical life at Un, In (service cycles)	100000.0 cycles
	Operating voltage	192 - 264 V
	Material contact	Silver nickel
	Suitable for plug-in socket mounting	Yes
MECHANICAL	Degree of protection (IP)	IP40
	Mechanical life (service cycles)	2.0E7 cycles
	Shock acceleration (Max)	50.0 g
	Vibration acceleration (Max)	5.0 m/s ²
DIMENSIONS	Width	32.8 mm
	Height	36.5 mm
	Depth	54.1 mm
ENVIRONMENT	Operating temperature	-40 - 70 °C