Product data sheet Characteristics

A9C18308

Acti9 double control input auxiliary iACTc 230...240 V AC



Main

Range	Acti9	
Product or component type	Double control input auxiliary	
Device short name	IACTc	
[Uc] control circuit voltage	230240 V AC 50/60 Hz impulse 250 ms 230240 V AC 50/60 Hz maintained	
[Us] rated supply voltage	220240 V AC at 50/60 Hz	

Complementary

•	
Maximum output current	0.2 A holding 2 A inrush
Hold-in power consumption in VA	3 VA
Mounting mode	Fixed, on the left of CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 Mm
Width	18 Mm
Depth	60 Mm
Colour	White
Overvoltage category	III
[Uimp] rated impulse withstand voltage	4 KV
[Ui] rated insulation voltage	440 V
Standards	IEC/EN 61095
Connections - terminals	Control circuit: tunnel type terminals 2 cable(s) 2.5 mm² flexible Control circuit: tunnel type terminals 2 cable(s) 1.5 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 1.52.5 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 1.52.5 mm² flexible with ferrule Control circuit: yellow clips
Wire stripping length	9 Mm
Tightening torque	0.8 N.M
Range compatibility	Acti9 (Acti9 iCT)
Market segment	Small commercial Residential
Compatibility code	IACTc

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-550 °C
Ambient air temperature for storage	-4070 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 Cm
Package 1 Width	7.9 Cm
Package 1 Length	9.0 Cm
Package 1 Weight	86.0 G
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Height	15.0 Cm
Package 2 Width	15.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	2.277 Kg

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

Warrantv	18 months	
vvarranty	18 months	

Product Life Status : Commercialised