
## 100C16F01

Allen-Bradley 100C Contactor 7.5kW 3Pole 230VAC Coil 1NC Contact Auxiliary





Component type	Power contactor, AC switching		
Range	100C		
Model	N/A		
Product status	Existing		

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

ELECTRICAL	Number of normally open contacts as main contact	3.0
	Number of normally closed contacts as main contact	0.0
	Rated operation current le at AC-3, 400 V	16.0 A
	Rated operation power at AC-3, 400 V	7.5 kW
	Rated operation current le at AC-1, 400 V	32.0 A
	Max. rated operation voltage Ue AC	690.0 V
	Voltage type for actuating	AC
	Rated control supply voltage Us at AC 50HZ	200 - 230 V
	Number of auxiliary contacts as normally open contact	0.0
	Number of auxiliary contacts as normally closed contact	1.0
	Rated operation current le at AC-3, 690 V	9.0 A
	Rated operation power at AC-3, 690 V	7.5 kW
	Rated operation power at AC-4, 400 V	4.0 kW
	Control supply voltage Us at AC 60HZ	260.0 V
	Power consumption, AC coil pickup	75.0 VA
	Power consumption, AC coil hold-in	9.5 VA
	Type of electrical connection of main circuit	Screw connection
	Rated operation current le at AC-4, 400 V	9.0 A
CONSTRUCTION	Degree of protection (IP)	IP20
	Mounting method	DIN-rail/screw
DIMENSIONS	Height	81.0 mm
	Width	45.0 mm
	Depth	86.5 mm
	Weight	0.39 kg



## **DIMENSIONAL DIAGRAM**

