100C23KJ01

Allen-Bradley 100C Contactor 11kW 3Pole 24VAC 50 and 60Hz Coil 1NC Contact Auxiliary





| Component type | Power contactor, AC switching | |
|----------------|-------------------------------|--|
| Range | 100C | |
| Model | N/A | |
| Product status | Existing | |

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

| ELECTRICAL | Number of normally open contacts as main contact | 3.0 |
|--------------|---|------------------|
| | Number of normally closed contacts as main contact | 0.0 |
| | Rated operation current le at AC-3, 400 V | 23.0 A |
| | Rated operation power at AC-3, 400 V | 11.0 kW |
| | Rated operation current le at AC-1, 400 V | 32.0 A |
| | Max. rated operation voltage Ue AC | 690.0 V |
| | Voltage type for actuating | AC |
| | Control supply voltage Us at AC 50HZ | 24.0 V |
| | Number of auxiliary contacts as normally open contact | 0.0 |
| | Number of auxiliary contacts as normally closed contact | 1.0 |
| | Rated operation current le at AC-3, 690 V | 12.0 A |
| | Rated operation power at AC-3, 690 V | 10.0 kW |
| | Rated operation power at AC-4, 400 V | 4.0 kW |
| | Control supply voltage Us at AC 60HZ | 24.0 V |
| | Power consumption, AC coil pickup | 75.0 VA |
| | Power consumption, AC coil hold-in | 9.5 VA |
| | Type of electrical connection of main circuit | Screw connection |
| | Rated operation current le at AC-4, 400 V | 9.0 A |
| CONSTRUCTION | Degree of protection (IP) | IP20 |
| | Mounting method | DIN-rail/screw |
| DIMENSIONS | Height | 81.0 mm |
| | Width | 45.0 mm |
| | Depth | 86.5 mm |
| | Weight | 0.39 kg |



DIMENSIONAL DIAGRAM

