100C43KD00

Allen-Bradley 100C Contactor 22kW 3Pole 110VAC 50 and 60Hz





Component type	Power contactor, AC switching	
Range	100C	
Model	N/A	
Alternative	CALL FOR ALTERNATIVE	

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

	Number of normally open contacts as main	
ELECTRICAL	contact	3.0
	Number of normally closed contacts as main contact	0.0
	Rated operation current le at AC-3, 400 V	43.0 A
	Rated operation power at AC-3, 400 V	22.0 kW
	Rated operation current le at AC-1, 400 V	85.0 A
	Max. rated operation voltage Ue AC	690.0 V
	Voltage type for actuating	AC
	Control supply voltage Us at AC 50HZ	110.0 V
	Number of auxiliary contacts as normally open contact	0.0
	Number of auxiliary contacts as normally closed contact	0.0
	Rated operation current le at AC-3, 690 V	25.0 A
	Rated operation power at AC-3, 690 V	22.0 kW
	Rated operation power at AC-4, 400 V	6.3 kW
	Control supply voltage Us at AC 60HZ	110.0 V
	Power consumption, AC coil pickup	135.0 VA
	Power consumption, AC coil hold-in	13.3 VA
	Type of electrical connection of main circuit	Screw connection
	Rated operation current le at AC-4, 400 V	14.0 A
CONSTRUCTION	Degree of protection (IP)	IP20
	Mounting method	DIN-rail/screw
DIMENSIONS	Height	81.0 mm
	Width	54.0 mm
	Depth	107.0 mm
	Weight	0.53 kg



DIMENSIONAL DIAGRAM

