

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable connector, CA, straight, shielded: yes, SPEEDCON locking, M23, No. of pos.: 8+1, Direction of rotation: Standard, type of contact: Pin, Solder connection, cable diameter range: 4 mm ... 6 mm, coding:N



Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Solder connection: proven connection technology for various litz wires

Commercial Data

Item number	1619570
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABRBFH
Product Key	ABRBFH
Catalog Page	Page 84 (C-2-2019)
GTIN	4046356823043
Weight per Piece (including packing)	100 g
Weight per Piece (excluding packing)	98.9 g
Customs tariff number	85366990
Country of origin	DE

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Technical Data

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Connector

Insulating body

Coding	N
Insulation body material	PBT
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact type	Pin
Application	Signal
Number of positions	9
Direction of rotation	Standard
Connection profile	8+1
Contact diameter Power contacts	2 mm
Litz wire cross-section Power contacts max.	2.5 mm ²
Rated current Power contacts	20 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts max.	1 mm ²
Nominal current per signal contact	8 A

Housing

Housing material	CuZn, GD-Zn
Type of locking	SPEEDCON locking
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	4 mm ... 6 mm
-------------------------	---------------

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Seal material	NBR
---------------	-----

Cable connector - CA-09P1N128006S




1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Drawings

Dimensional drawing




Cable connector - CA-09P1N128006S




1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Approvals

 cUL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Power	48 V	12 A	- 14	-
Signal	48 V	6 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Power	48 V	20 A	- 14	-
Signal	48 V	8 A	- 18	-

cULus Recognized				
-------------------------	--	--	--	--

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Classifications

ECLASS

ECLASS-9.0	27440102
ECLASS-10.0.1	27440102
ECLASS-11.0	27440102

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Cable connector - CA-09P1N128006S



1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Accessories

Torque screwdriver

Torque screwdriver - SF-Z0028 - 1607456

<https://www.phoenixcontact.com/gb/products/1607456>

Torque screwdriver, series: RC



Hook wrench

Hook wrench - SF-Z0027 - 1607455

<https://www.phoenixcontact.com/gb/products/1607455>

Hook wrench, series: RC



Cable connector - CA-09P1N128006S

1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Protective cap

Protective cap - RC-Z2058 - 1604223

<https://www.phoenixcontact.com/gb/products/1604223>

Plastic protection cap for connectors with M23 knurled nut



Plastic anti-static dust protection cap

Plastic anti-static dust protection cap - RC-Z2468 - 1611796

<https://www.phoenixcontact.com/gb/products/1611796>

Plastic protection cap, antistatic, for connectors with M23 knurled nut



Cable connector - CA-09P1N128006S

1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Color-coding

Color-coding - RF-Z0014 - 1620588

<https://www.phoenixcontact.com/gb/products/1620588>

Color-coding, color: green



Color-coding

Color-coding - RF-Z0015 - 1620592

<https://www.phoenixcontact.com/gb/products/1620592>

Color-coding, color: orange



Cable connector - CA-09P1N128006S

1619570

<https://www.phoenixcontact.com/gb/products/1619570>

Color-coding

Color-coding - RF-Z0016 - 1620593

<https://www.phoenixcontact.com/gb/products/1620593>

Color-coding, color: black



Square mounting flange

Square mounting flange - RF-Z0003 - 1607905

<https://www.phoenixcontact.com/gb/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF

Cable connector - CA-09P1N128006S

1619570

<https://www.phoenixcontact.com/gb/products/1619570>



Metal protective cap

Metal protective cap - CA-Z0077 - 1627224

<https://www.phoenixcontact.com/gb/products/1627224>



Metal protection cap with steel wire and loop, for M23 signal connectors with knurled nut for fastening to the cable

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk