Specifications



TeSys Deca - auxiliary contact - 2 NO

GVAE20

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys TeSys Deca	
Device short name	GVAE	
Product or Component Type	Auxiliary contact block	
Product Compatibility	GV2L GV3P GV2ME LS1D32 GV3L GV2RT GV2P GV2LE	
Mounting Location	Front side	
Pole contact composition	2 NO	
Quantity per Set	Set of 10	

Complementary

[Ui] rated insulation voltage	300 V UL 508 300 V CSA C22.2 No 14 250 V IEC 60947-1	
[Ue] rated operational voltage	24240 V AC 2460 V DC	
[Ith] conventional free air thermal current	2.5 A	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A	
Rated operational power in VA	120 VA 110120 V AC-15 100000 cycles 120 VA 230240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles	
Rated operational power in W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles	
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals	
Height	0.4 in (11 mm)	
Width	1.8 in (45 mm)	
Depth	1.1 in (29 mm)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Net Weight

0.04 lb(US) (0.02 kg)

Environment

Environmental characteristic	Normal environment	
Product Certifications	UKCA	

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0111
GTIN	3389110343465
Returnability	Yes
Country of origin	US

Packing Units

U		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.63 in (1.600 cm)	
Package 1 Width	1.97 in (5.000 cm)	
Package 1 Length	2.36 in (6.000 cm)	
Package 1 Weight	0.670 oz (19.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	2.48 in (6.300 cm)	
Package 2 Width	2.87 in (7.300 cm)	
Package 2 Length	4.72 in (12.000 cm)	
Package 2 Weight	7.372 oz (209.000 g)	
Unit Type of Package 3	S02	
Number of Units in Package 3	220	
Package 3 Height	5.91 in (15.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	9.650 lb(US) (4.377 kg)	

Contractual warranty

Warranty

18 months

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal O}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

[⊗] Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product data sheet

Connections and Schema

GVAE20

