Product datasheet

Specifications



(!) Discontinued

Main

Range	TeSys	
Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
Contactor application	Resistive load Motor control	
Utilisation category	AC-1 AC-4 AC-3	
Poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	
[le] rated operational current	9 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 20 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	5 V DC	

() Discontinued on: 1 Nov 2020

LC1D093AL

TeSys D contactor - 3P(3 NO) -AC-3 - <= 440 V 9 A - 5 V DC coil

Complementary

Motor power kW	2.2 kW at 220230 V AC 50/60 Hz (AC-3)
	4 kW at 380400 V AC 50/60 Hz (AC-3)
	4 kW at 415440 V AC 50/60 Hz (AC-3)
	5.5 kW at 500 V AC 50/60 Hz (AC-3)
	5.5 kW at 660690 V AC 50/60 Hz (AC-3)
	2.2 kW at 400 V AC 50/60 Hz (AC-4)
Motor power hp	1 hp at 230/240 V AC 50/60 Hz for 1 phase motors
	2 hp at 200/208 V AC 50/60 Hz for 3 phases motors
	2 hp at 230/240 V AC 50/60 Hz for 3 phases motors
	5 hp at 460/480 V AC 50/60 Hz for 3 phases motors
	7.5 hp at 575/600 V AC 50/60 Hz for 3 phases motors
	0.33 hp at 115 V AC 50/60 Hz for 1 phase motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal	10 A (at 60 °C) for signalling circuit
current	16 A (at 60 °C) for power circuit
Irms rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947
	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947

[Icw] rated short-time withstand current	105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 25 A gG at <= 690 V coordination type 1 for power circuit 20 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2.5 mOhm - Ith 16 A 50 Hz for power circuit	
Power dissipation per pole	1.56 W AC-1 0.2 W AC-3	
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
Overvoltage category	III	
pollution degree	3	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Mechanical durability	30 Mcycles	
Electrical durability	0.6 Mcycles 25 A AC-1 at Ue <= 440 V 2 Mcycles 9 A AC-3 at Ue <= 440 V	
Control circuit type	DC low consumption	
Coil technology	Built-in bidirectional peak limiting diode suppressor	
Control circuit voltage limits	0.10.3 Uc (-4070 °C):drop-out DC 0.81.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC	
Inrush power in W	2.4 W (at 20 °C)	
Hold-in power consumption in W	2.4 W at 20 °C	
Operating time	77 ±15 % ms closing 25 ±20 % ms opening	
Time constant	40 ms	
Connections - terminals	Power circuit: spring terminals 1 2.5 mm ² - cable stiffness: flexible without cable end Power circuit: spring terminals 2 2.5 mm ² - cable stiffness: flexible without cable end Control circuit: spring terminals 1 2.5 mm ² - cable stiffness: flexible without cable end Control circuit: spring terminals 2 2.5 mm ² - cable stiffness: flexible without cable end	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching voltage	17 V for signalling circuit	
Minimum switching current	5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Rail Plate	

Environment

CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508	
LROS (Lloyds register of shipping) GOST RINA BV CSA CCC UL GL DNV	
IP20 front face conforming to IEC 60529	
TH conforming to IEC 60068-2-30	
conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
-4060 °C 6070 °C with derating	
03000 m	
850 °C conforming to IEC 60695-2-1	
V1 conforming to UL 94	
Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)	
80 mm	
45 mm	
95 mm	
0.48 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	10.5 cm
Package 1 Length	5.4 cm
Package 1 Weight	505 g

Contractual warranty

Warranty

12 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances				
EU RoHS Directive	Compliant			
PVC free	Yes			
Use Again				
igvarrow Repack and remanufacture				

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

WEEE