

# LC1D09KUE

TeSys D Green IEC contactor, 9 A, 3 P, 5 HP  
at 480 VAC, nonreversing, 100-250 VAC/VDC  
coil





## Main

|                                             |                                                                                                                                                                                                                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                       | TeSys                                                                                                                                                                                                                                                                    |
| Product name                                | TeSys D Green                                                                                                                                                                                                                                                            |
| Product or component type                   | Contacteur                                                                                                                                                                                                                                                               |
| Device short name                           | LC1D                                                                                                                                                                                                                                                                     |
| Contacteur application                      | Motor control<br>Resistive load                                                                                                                                                                                                                                          |
| Utilisation category                        | AC-1<br>AC-3                                                                                                                                                                                                                                                             |
| Poles description                           | 3P                                                                                                                                                                                                                                                                       |
| Power pole contact composition              | 3 NO                                                                                                                                                                                                                                                                     |
| [Ue] rated operational voltage              | Power circuit <= 690 V AC 25...400 Hz                                                                                                                                                                                                                                    |
| [Ie] rated operational current              | 9 A 140 °F (60 °C)) <= 440 V AC-3 power circuit<br>25 A 140 °F (60 °C)) <= 440 V AC-1 power circuit                                                                                                                                                                      |
| Motor power kW                              | 2.2 KW 220...230 V AC 50 Hz AC-3)<br>4 KW 380...400 V AC 50 Hz AC-3)<br>4 KW 415 V AC 50 Hz AC-3)<br>4 KW 440 V AC 50 Hz AC-3)<br>5.5 KW 500 V AC 50 Hz AC-3)<br>5.5 kW 660...690 V AC 50 Hz AC-3)                                                                       |
| Motor power HP (UL / CSA)                   | 0.33 Hp 115 V AC 60 Hz 1 phase<br>1 Hp 230/240 V AC 60 Hz 1 phase<br>2 Hp 200/208 V AC 60 Hz 3 phase<br>2 Hp 230/240 V AC 60 Hz 3 phase<br>5 Hp 460/480 V AC 60 Hz 3 phase<br>7.5 hp 575/600 V AC 60 Hz 3 phase                                                          |
| [Uc] control circuit voltage                | 100...250 V AC 50/60 Hz<br>100...250 V DC                                                                                                                                                                                                                                |
| Coil type                                   | AC/DC electronic                                                                                                                                                                                                                                                         |
| Auxiliary contact composition               | 1 NO + 1 NC                                                                                                                                                                                                                                                              |
| [Uimp] rated impulse withstand voltage      | 6 kV IEC 60947                                                                                                                                                                                                                                                           |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                      |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C) signalling circuit<br>25 A (at 60 °C) for power circuit                                                                                                                                                                                              |
| Irms rated making capacity                  | 250 A at 440 V for power circuit conforming to IEC 60947<br>140 A AC signalling circuit IEC 60947-5-1<br>250 A DC signalling circuit IEC 60947-5-1                                                                                                                       |
| Rated breaking capacity                     | 250 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                 |
| [Icw] rated short-time withstand current    | 100 A - 1 s signalling circuit<br>120 A - 500 ms signalling circuit<br>140 A - 100 ms signalling circuit<br>30 A 40 °C - 10 min for power circuit<br>61 A 40 °C - 1 min for power circuit<br>105 A 40 °C - 10 s for power circuit<br>210 A 40 °C - 1 s for power circuit |
| Associated fuse rating                      | 10 A gG signalling circuit IEC 60947-5-1<br>25 A gG at <= 690 V coordination type 1 for power circuit<br>20 A gG at <= 690 V coordination type 2 for power circuit                                                                                                       |
| Average impedance                           | 2.5 mOhm - Ith 25 A 50 Hz for power circuit                                                                                                                                                                                                                              |
| [Ui] rated insulation voltage               | Power circuit 690 V IEC 60947-4-1<br>Signalling circuit 690 V IEC 60947-1                                                                                                                                                                                                |
| Electrical durability                       | 2.4 Mcycles 8 A AC-3 <= 440 V<br>0.6 Mcycles 25 A AC-1 <= 440 V                                                                                                                                                                                                          |
| Power dissipation per pole                  | 1.56 W AC-1<br>0.2 W AC-3                                                                                                                                                                                                                                                |
| Front cover                                 | With                                                                                                                                                                                                                                                                     |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting support         | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Standards                | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Product certifications   | CCC<br>CSA<br>EAC<br>UL<br>KC<br>DNV-GL<br>LROS (Lloyds register of shipping)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Connections - terminals  | Control circuit screw clamp terminals 1 0.00...<br>0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 2 0.00...<br>0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 1 0.00...<br>0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 2 0.00...<br>0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 1 0.00...<br>0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid<br>Control circuit screw clamp terminals 2 0.00...<br>0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid<br>Power circuit: screw clamp terminals 1 cable(s) 1...<br>4 mm <sup>2</sup> flexible without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 1...<br>4 mm <sup>2</sup> flexible without cable end<br>Power circuit: screw clamp terminals 1 cable(s) 1...<br>4 mm <sup>2</sup> flexible with cable end<br>Power circuit: screw clamp terminals 2 cable(s) 1...<br>2.5 mm <sup>2</sup> flexible with cable end<br>Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup><br>(1...4 mm <sup>2</sup> )solid<br>Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup><br>(1...4 mm <sup>2</sup> )solid |
| Tightening torque        | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp<br>terminals flat Ø 6 mm<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp<br>terminals Philips No 2<br>Power circuit: 1.7 N.m - on screw clamp terminals -<br>with screwdriver flat Ø 6 mm<br>Power circuit: 1.7 N.m - on screw clamp terminals -<br>with screwdriver Philips No 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Operating time           | 45...55 ms closing<br>20...90 ms opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load<br>EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical<br>load EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mechanical durability    | 15 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Maximum operating rate   | 3600 cyc/h 140 °F (60 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

## Complementary

|                                 |                                                                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                 | Built-in bidirectional peak limiting                                                                                                                                        |
| Control circuit voltage limits  | <= 0.1 Uc -40...158 °F (-40...70 °C) drop-out AC/DC<br>0.85...1.1 Uc -40...140 °F (-40...60 °C) operational AC/DC<br>1...1.1 Uc 140...158 °F (60...70 °C) operational AC/DC |
| Inrush power in VA              | 25 VA 50/60 Hz 68 °F (20 °C))                                                                                                                                               |
| Inrush power in W               | 18 W 68 °F (20 °C)                                                                                                                                                          |
| Hold-in power consumption in VA | 1.6 VA 68 °F (20 °C)) 50/60 Hz                                                                                                                                              |
| Hold-in power consumption in W  | 1.1 W 68 °F (20 °C)                                                                                                                                                         |
| Heat dissipation                | 1.1 W 50/60 Hz                                                                                                                                                              |
| Auxiliary contacts type         | Mechanically linked 1 NO + 1 NC IEC 60947-5-1<br>Mirror contact 1 NC IEC 60947-4-1                                                                                          |
| Signalling circuit frequency    | 25...400 Hz                                                                                                                                                                 |
| Minimum switching current       | 5 mA signalling circuit                                                                                                                                                     |
| Minimum switching voltage       | 17 V signalling circuit                                                                                                                                                     |

|                       |                                                                                                         |
|-----------------------|---------------------------------------------------------------------------------------------------------|
| Non-overlap time      | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact |
| Insulation resistance | > 10 MOhm signalling circuit                                                                            |
| Compatibility code    | LC1D                                                                                                    |

## Environment

|                                       |                                                                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection               | IP20 front face IEC 60529                                                                                                                                                  |
| Protective treatment                  | TH IEC 60068-2-30                                                                                                                                                          |
| Pollution degree                      | 3                                                                                                                                                                          |
| Ambient air temperature for operation | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating                                                                                                      |
| Ambient air temperature for storage   | -76...176 °F (-60...80 °C)                                                                                                                                                 |
| Operating altitude                    | 0...9842.52 ft (0...3000 m)                                                                                                                                                |
| Fire resistance                       | 1562 °F (850 °C) IEC 60695-2-1                                                                                                                                             |
| Flame retardance                      | V1 UL 94                                                                                                                                                                   |
| Mechanical robustness                 | Vibrations contactor open2 Gn, 5...300 Hz<br>Vibrations contactor closed4 Gn, 5...300 Hz<br>Shocks contactor open10 Gn for 11 ms<br>Shocks contactor closed15 Gn for 11 ms |
| Height                                | 3.03 in (77 mm)                                                                                                                                                            |
| Maximum Width                         | 1.77 in (45 mm)                                                                                                                                                            |
| Depth                                 | 3.39 in (86 mm)                                                                                                                                                            |
| Net Weight                            | 0.81 lb(US) (0.368 kg)                                                                                                                                                     |
| Color                                 | Gray SE GREY 6)<br>Green SE GREEN 2)                                                                                                                                       |

## Ordering and shipping details

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Category              | 22356 - CTR, TESYS D, OPEN, 9-65A AC/DC GREEN |
| Discount Schedule     | I12                                           |
| GTIN                  | 00785901965732                                |
| Nbr. of units in pkg. | 1                                             |
| Package weight(Lbs)   | 0.81 lb(US) (0.37 kg)                         |
| Returnability         | Yes                                           |
| Country of origin     | FR                                            |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 2.17 in (5.5 cm)        |
| Package 1 width              | 3.74 in (9.5 cm)        |
| Package 1 Length             | 4.72 in (12 cm)         |
| Unit Type of Package 2       | S02                     |
| Number of Units in Package 2 | 15                      |
| Package 2 Weight             | 13.86 lb(US) (6.288 kg) |
| Package 2 Height             | 5.91 in (15 cm)         |
| Package 2 width              | 11.81 in (30 cm)        |
| Package 2 Length             | 15.75 in (40 cm)        |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                               |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |

|                             |                                                                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile         | <a href="#"> End Of Life Information</a>     |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Halogen content performance | Halogen free plastic parts & cables product                                                                                  |
| <b>Contractual warranty</b> |                                                                                                                              |
| Warranty                    | 18 months                                                                                                                    |