# **Product datasheet**

Specifications



# TeSys D contactor - 3P(3 NO) -AC-3 - <= 440 V 115 A - 220 V DC

standard coil

Local distributor code: 386021703

LC1D115MD

#### EAN Code: 3389110377149

### Main

Range	TeSys
Range of product	TeSys Deca
Product or component type	Contactor
Device short name	LC1D
Contactor application	Motor control Resistive load
Utilisation category	AC-4 AC-1 AC-3 AC-3e
Poles description	3P
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 300 V DC
[le] rated operational current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 115 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 115 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	220 V DC

[Uc] control circuit voltage

## Complementary

Motor power kW	30 kW at 220230 V AC 50/60 Hz (AC-3)	
	55 kW at 380400 V AC 50/60 Hz (AC-3)	
	59 kW at 415440 V AC 50/60 Hz (AC-3)	
	75 kW at 500 V AC 50/60 Hz (AC-3)	
	80 kW at 660690 V AC 50/60 Hz (AC-3)	
	65 kW at 1000 V AC 50/60 Hz (AC-3)	
	18.5 kW at 400 V AC 50/60 Hz (AC-4)	
	30 kW at 220230 V AC 50/60 Hz (AC-3e)	
	55 kW at 380400 V AC 50/60 Hz (AC-3e)	
	59 kW at 415440 V AC 50/60 Hz (AC-3e)	
	75 kW at 500 V AC 50/60 Hz (AC-3e)	
	80 kW at 660690 V AC 50/60 Hz (AC-3e)	
	65 kW at 1000 V AC 50/60 Hz (AC-3e)	
Motor power hp	30 hp at 200/208 V AC 50/60 Hz for 3 phases motors	
	40 hp at 230/240 V AC 50/60 Hz for 3 phases motors	
	75 hp at 460/480 V AC 50/60 Hz for 3 phases motors	
	100 hp at 575/600 V AC 50/60 Hz for 3 phases motors	
Compatibility code	LC1D	
Pole contact composition	3 NO	
Protective cover	With	
[Ith] conventional free air thermal current	200 A (at 60 °C) for power circuit	
Irms rated making capacity	1260 A at 440 V for power circuit conforming to IEC 60947	
	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	

1100 A at 440 V for power circuit conforming to IEC 60947	
250 A 40 °C - 10 min for power circuit 550 A 40 °C - 1 min for power circuit 950 A 40 °C - 10 s for power circuit 1100 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
250 A gG at <= 690 V coordination type 1 for power circuit 200 A gG at <= 690 V coordination type 2 for power circuit 10 A gG for signalling circuit	
0.6 mOhm - Ith 200 A 50 Hz for power circuit	
24 W AC-1 7.9 W AC-3 7.9 W AC-3e	
Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
III	
3	
8 kV conforming to IEC 60947	
B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
8 Mcycles	
0.8 Mcycles 200 A AC-1 at Ue <= 440 V 0.95 Mcycles 115 A AC-3 at Ue <= 440 V 0.95 Mcycles 115 A AC-3e at Ue <= 440 V	
DC standard	
With integral suppression device	
0.751.2 Uc (-4055 °C):operational DC 0.150.4 Uc (-4070 °C):drop-out DC 11.2 Uc (5570 °C):operational DC	
270365 W (at 20 °C)	
2.45.1 W at 20 °C	
2035 ms closing 4075 ms opening	
25 ms	
1200 cyc/h at 60 °C	
Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 2 1050 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: connector 1 10120 mm <sup>2</sup> - cable stiffness: flexible without cable end	

Tightening torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat $\emptyset$ 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching voltage	17 V for signalling circuit	
Minimum switching current	5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Plate Rail	

## Environment

Standards	CSA C22.2 No 14	
	EN 60947-4-1	
	IEC 60947-4-1	
	IEC 60335-1:Clause 30.2	
	IEC 60335-2-40:Annex JJ	
	UL 60335-2-40:Annex JJ	
	UL 60947-4-1	
	CSA C22.2 No 60947-4-1	
	JIS C8201-4-1	
	JIS C6201-4-1	
Product certifications	UL	
	CSA	
	CCC	
	UKCA	
	CE	
	EAC	
	Marine	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat	
	conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
Permissible ambient air	-4060 °C	
temperature around the device	6070 °C with derating	
-		
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz)	
	Vibrations contactor closed (4 Gn, 5300 Hz)	
	Shocks contactor closed (15 Gn for 11 ms)	
	Shocks contactor open (6 Gn for 11 ms)	
Height	158 mm	
Width	120 mm	
Depth	136 mm	
Net weight	2.5 kg	

# **Packing Units**

Unit Type of Package 1

PCE

Number of Units in Package 1	1
Package 1 Height	16.900 cm
Package 1 Width	19.600 cm
Package 1 Length	20.800 cm
Package 1 Weight	2.502 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	10.766 kg

# Logistical informations

Country of origin

CZ

# **Contractual warranty**

Warranty

18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

#### 

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	94
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

<sup>⊗</sup> Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	A530c666-91dd-4119-8d61-f1c22a361ecb
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
PVC free	Yes

#### Use Again

Circularity Profile End of Life Information   WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   Take-back No	○ Repack and remanufacture	
up in rubbish bins	Circularity Profile	End of Life Information
Take-back No	WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
	Take-back	Νο