

# TeSys D contactor - 4P(2 NO + 2 NC) - AC-1 - <= 440 V 40 A - 110 V AC coil

Local distributor code:

386076509 LC1D258F7

EAN Code: 3389110577495

## Main

Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
Contactor application	Resistive load	
Utilisation category	AC-1	
Poles description	4P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz	
[le] rated operational current	40 A (at <60 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	110 V AC 50/60 Hz	

## Complementary

Compatibility code	LC1D	
Pole contact composition	2 NO + 2 NC	
Protective cover	With	
[Ith] conventional free air thermal current	10 A (at 60 °C) for signalling circuit 40 A (at 60 °C) for power circuit	
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 450 A at 440 V for power circuit conforming to IEC 60947	
Rated breaking capacity	450 A at 440 V for power circuit conforming to IEC 60947	
[Icw] rated short-time withstand current	240 A 40 °C - 10 s for power circuit 380 A 40 °C - 1 s for power circuit 50 A 40 °C - 10 min for power circuit 120 A 40 °C - 1 min for power circuit 120 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 40 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2 mOhm - Ith 40 A 50 Hz for power circuit	
Power dissipation per pole	3.2 W AC-1	
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
overvoltage category	III	

B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  15 Mcycles  1.4 Mcycles 40 A AC-1 at Ue <= 440 V  AC at 50/60 Hz  Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.3 (at 20 °C) 77 VA 50 Hz cos phi 0.3 (at 20 °C) 23 W at 50/60 Hz	
B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  15 Mcycles  1.4 Mcycles 40 A AC-1 at Ue <= 440 V  AC at 50/60 Hz  Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz  0.81.1 Uc (-4060 °C):operational AC 50 Hz  0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C)  70 VA 50 Hz cos phi 0.3 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  23 W at 50/60 Hz	
B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  15 Mcycles  1.4 Mcycles 40 A AC-1 at Ue <= 440 V  AC at 50/60 Hz  Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz  0.81.1 Uc (-4060 °C):operational AC 50 Hz  0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C)  70 VA 50 Hz cos phi 0.3 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  23 W at 50/60 Hz	
1.4 Mcycles 40 A AC-1 at Ue <= 440 V  AC at 50/60 Hz  Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz  0.81.1 Uc (-4060 °C):operational AC 50 Hz  0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C)  70 VA 50 Hz cos phi 0.75 (at 20 °C)  7.5 VA 60 Hz cos phi 0.3 (at 20 °C)  7.5 VA 50 Hz cos phi 0.3 (at 20 °C)  23 W at 50/60 Hz	
AC at 50/60 Hz  Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz  0.81.1 Uc (-4060 °C):operational AC 50 Hz  0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C)  70 VA 50 Hz cos phi 0.75 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  23 W at 50/60 Hz	
Without built-in suppressor module  0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz  0.81.1 Uc (-4060 °C):operational AC 50 Hz  0.851.1 Uc (-4060 °C):operational AC 60 Hz  70 VA 60 Hz cos phi 0.75 (at 20 °C)  70 VA 50 Hz cos phi 0.75 (at 20 °C)  7.5 VA 60 Hz cos phi 0.3 (at 20 °C)  7 VA 50 Hz cos phi 0.3 (at 20 °C)  23 W at 50/60 Hz	
0.30.6 Uc (-4060 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C) 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C) 23 W at 50/60 Hz	
0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C) 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C) 23 W at 50/60 Hz	
70 VA 50 Hz cos phi 0.75 (at 20 °C) 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C) 23 W at 50/60 Hz	
7 VA 50 Hz cos phi 0.3 (at 20 °C) 23 W at 50/60 Hz	
1222 ms closing	
1222 ms closing 419 ms opening	
3600 cyc/h at 60 °C	
Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 2.510 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 2.510 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 2.510 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 2.516 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 2.516 mm² - cable stiffness: solid without cable end	
Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 1.8 N.m - on screw clamps terminals - with screwdriver flat Ø 6 mm Power circuit: 1.8 N.m - on screw clamps terminals - with screwdriver Philips No 2 Power circuit: 1.8 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
1 NO + 1 NC	
type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
25400 Hz	
25400 Hz 17 V for signalling circuit	
17 V for signalling circuit	
_	

Rail		
Plate		
	Rail Plate	

## **Environment**

LIMITOTITIETIL		
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-4-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ CSA C22.2 No 60947-4-1	
Product certifications	UL CCC CSA Marine UKCA EAC CB Scheme	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (8 Gn for 11 ms)	
Height	91 mm	
Width	45 mm	
Depth	99 mm	
Net weight	0.425 kg	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.800 cm
Package 1 Width	9.500 cm
Package 1 Length	12.000 cm
Package 1 Weight	468.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	16
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm

Package 2 Weight	8.021 kg
Unit Type of Package 3	P06
Number of Units in Package 3	128
Package 3 Height	45.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	72.168 kg

# Logistical informations

Country of origin

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	138
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
PVC free	Yes

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No