



Price\* : 193.00 USD



## Main

|                                |  |
|--------------------------------|--|
| Range                          | TeSys  |
| Product name                   | TeSys D  |
| Product or component type      | Contactor  |
| Device short name              | LC1D   |
| Contactor application          | Motor control<br>Resistive load  |
| Utilisation category           | AC-4<br>AC-1<br>AC-3   |
| Poles description              | 3P   |
| Power pole contact composition | 3 NO   |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit <= 300 V DC  |
| [Ie] rated operational current | 50 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>38 A (at <60 °C) at <= 440 V AC AC-3 for power circuit   |
| Motor power kW                 | 18.5 kW at 500 V AC 50/60 Hz (AC-3)<br>18.5 kW at 660...690 V AC 50/60 Hz (AC-3)<br>7.5 kW at 400 V AC 50/60 Hz (AC-4)<br>18.5 kW at 380...400 V AC 50/60 Hz (AC-3)<br>9 kW at 220...230 V AC 50/60 Hz (AC-3)<br>18.5 kW at 415...440 V AC 50/60 Hz (AC-3)   |
| Motor power HP (UL / CSA)      | 10 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>10 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>5 hp at 240 V AC 50/60 Hz for 1 phase motors<br>20 hp at 480 V AC 50/60 Hz for 3 phases motors<br>25 hp at 600 V AC 50/60 Hz for 3 phases motors |
| Control circuit type           | AC 50/60 Hz  |
| [Uc] control circuit voltage   | 380 V AC 50/60 Hz  |
| Auxiliary contact composition  | 1 NO + 1 NC  |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|   |   |
|---|---|
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947  |
| Overvoltage category                        | III   |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C) signalling circuit<br>50 A 140 °F (60 °C) power circuit   |
| Irms rated making capacity                  | 140 A AC signalling circuit IEC 60947-5-1<br>250 A DC signalling circuit IEC 60947-5-1<br>550 A 440 V power circuit IEC 60947   |
| Rated breaking capacity                     | 550 A 440 V power circuit IEC 60947   |
| [Icw] rated short-time withstand current    | 60 A 104 °F (40 °C) - 10 min power circuit<br>430 A 104 °F (40 °C) - 1 s power circuit<br>150 A 104 °F (40 °C) - 1 min power circuit<br>310 A 104 °F (40 °C) - 10 s power circuit<br>100 A - 1 s signalling circuit<br>120 A - 500 ms signalling circuit<br>140 A - 100 ms signalling circuit   |
| Associated fuse rating                      | 10 A gG signalling circuit IEC 60947-5-1<br>63 A gG ≤ 690 V type 1 power circuit<br>63 A gG ≤ 690 V type 2 power circuit  |
| Average impedance                           | 2 mOhm - Ith 50 A 50 Hz power circuit   |
| [Ui] rated insulation voltage               | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit 690 V IEC 60947-1<br>Signalling circuit 600 V CSA<br>Signalling circuit 600 V UL<br>Power circuit 690 V IEC 60947-4-1   |
| Electrical durability                       | 1.4 Mcycles 50 A AC-1 at Ue ≤ 440 V<br>1.4 Mcycles 38 A AC-3 at Ue ≤ 440 V  |
| Power dissipation per pole                  | 5 W AC-1<br>3 W AC-3  |
| Front cover                                 | With  |
| Mounting support                            | Rail<br>Plate   |
| Standards                                   | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508   |
| Product certifications                      | UL<br>RINA<br>BV<br>GL<br>DNV<br>LROS (Lloyds register of shipping)<br>CSA<br>GOST<br>CCC   |
| Connections - terminals                     | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Power circuit screw clamp terminals 1 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )flexible without cable end<br>Power circuit screw clamp terminals 2 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )flexible without cable end<br>Power circuit screw clamp terminals 1 0.00...0.02 in <sup>2</sup> (1...10 mm <sup>2</sup> )flexible with cable end<br>Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> )flexible with cable end<br>Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm <sup>2</sup> solid without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 2.5...10 mm <sup>2</sup> solid without cable end |
| Tightening torque                           | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2  |
| Operating time                              | 4...19 ms opening<br>12...22 ms closing   |
| Safety reliability level                    | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |

|                        |                  |
|------------------------|------------------|
| Mechanical durability  | 15 Mcycles       |
| Maximum operating rate | 3600 cyc/h 60 °C |

## Complementary

|                                 |   |
|---------------------------------|---|
| Coil technology                 | Without built-in suppressor module  |
| Control circuit voltage limits  | 0.3...0.6 Uc -40...158 °F (-40...70 °C) drop-out AC 50/60 Hz<br>0.8...1.1 Uc -40...140 °F (-40...60 °C) operational AC 50 Hz<br>0.85...1.1 Uc -40...140 °F (-40...60 °C) operational AC 60 Hz<br>1...1.1 Uc 140...158 °F (60...70 °C) operational AC 50/60 Hz |
| Inrush power in VA              | 70 VA 60 Hz cos phi 0.75 (at 20 °C)<br>70 VA 50 Hz cos phi 0.75 (at 20 °C)  |
| Hold-in power consumption in VA | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C)<br>7 VA 50 Hz cos phi 0.3 (at 20 °C)  |
| Heat dissipation                | 2...3 W at 50/60 Hz   |
| Auxiliary contacts type         | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1  |
| Signalling circuit frequency    | 25...400 Hz   |
| Minimum switching current       | 5 mA signalling circuit   |
| Minimum switching voltage       | 17 V signalling circuit   |
| Non-overlap time                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact   |
| Insulation resistance           | > 10 MOhm signalling circuit  |
| Contact compatibility           | M2  |
| Compatibility code              | LC1D  |
| Motor power range               | 7...11 kW at 200...240 V 3 phases<br>15...25 kW at 380...440 V 3 phases<br>15...25 kW at 480...500 V 3 phases<br>15...25 kW at 525...690 V 3 phases<br>4...6 kW at 100...120 V 3 phases   |
| Motor starter type              | Direct on-line contactor  |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP20 front face IEC 60529   |
| Protective treatment                  | TH IEC 60068-2-30   |
| Pollution degree                      | 3   |
| Ambient air temperature for operation | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating   |
| Ambient air temperature for storage   | -76...176 °F (-60...80 °C)  |
| Operating altitude                    | 0...9842.52 ft (0...3000 m)   |
| Fire resistance                       | 850 °C conforming to IEC 60695-2-1  |
| Flame retardance                      | V1 conforming to UL 94  |
| Mechanical robustness                 | Vibrations contactor open2 Gn, 5...300 Hz<br>Vibrations contactor closed4 Gn, 5...300 Hz<br>Shocks contactor closed15 Gn for 11 ms<br>Shocks contactor open8 Gn for 11 ms |
| Height                                | 3.35 in (85 mm)   |
| Width                                 | 1.77 in (45 mm)   |
| Depth                                 | 3.62 in (92 mm)   |
| Net Weight                            | 0.84 lb(US) (0.38 kg)   |

## Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 22354 - CTR, TESYS D, OPEN, 9-38A AC |
| Discount Schedule     | I12                                  |
| GTIN                  | 03389110352658                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 0.81 lb(US) (0.37 kg)                |

|                   |    |
|-------------------|----|
| Returnability     | No |
| Country of origin | FR |

### Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 1.97 in (5 cm)          |
| Package 1 width              | 3.78 in (9.6 cm)        |
| Package 1 Length             | 4.41 in (11.2 cm)       |
| Unit Type of Package 2       | S02                     |
| Number of Units in Package 2 | 20                      |
| Package 2 Weight             | 18.95 lb(US) (8.597 kg) |
| Package 2 Height             | 5.91 in (15 cm)         |
| Package 2 width              | 11.81 in (30 cm)        |
| Package 2 Length             | 15.75 in (40 cm)        |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| PVC free                   | Yes   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|