

Product data sheet

Characteristics

LC1D65U7

IEC contactor, TeSys D, nonreversing, 65A, 40HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 240VAC 50/60Hz coil, open



Product availability: Stock - Normally stocked in distribution facility

Price*: 532.80 USD



Main

Range	TeSys
Range of Product	TeSys Deca TeSys D
Product or Component Type	Contactor
Device short name	LC1D
Contactor application	Resistive load Resistive load
Utilisation category	AC-4 AC-1 AC-2 AC-3e AC-3
Poles description	3P
[Ue] rated operational voltage	Power circuit ≤ 690 V AC 25...400 Hz
[Ie] rated operational current	65 A 140 °F (60 °C) ≤ 440 V AC AC-3 power circuit 65 A 140 °F (60 °C) ≤ 440 V AC AC-3e power circuit 65 A 140 °F (60 °C) 240 V AC AC-3 power circuit 80 A 140 °F (60 °C) 240 V AC AC-1 power circuit
[Uc] control circuit voltage	240 V AC 50/60 Hz

Complementary

Motor power kW	11 KW 400 V AC 50 Hz AC-4) 30 KW 380...400 V AC 50 Hz AC-3) 37 KW 500 V AC 50 Hz AC-3) 37 KW 660...690 V AC 50 Hz AC-3) 18.5 KW 220...230 V AC 50 Hz AC-3) 30 KW 415 V AC 50 Hz AC-3) 37 KW 1000 V AC 50 Hz AC-3) 30 KW 440 V AC 50 Hz AC-3e) 30 KW 380...400 V AC 50 Hz AC-3e) 37 KW 500 V AC 50 Hz AC-3e) 37 KW 660...690 V AC 50 Hz AC-3e) 18.5 KW 220...230 V AC 50 Hz AC-3e) 30 KW 415 V AC 50 Hz AC-3e) 37 KW 1000 V AC 50 Hz AC-3e) 37 KW 500 V AC 50 Hz 30 KW 380...400 V AC 50 Hz
Maximum Horse Power Rating	10 Hp 230/240 V at AC 60 Hz for 1 phase 20 Hp 200/208 V at AC 60 Hz for 3 phase 20 Hp 230/240 V at AC 60 Hz for 3 phase 40 Hp 460/480 V at AC 60 Hz for 3 phase 50 Hp 575/600 V at AC 60 Hz for 3 phase 5 Hp 115 V at AC 60 Hz for 1 phase
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal current	80 A 140 °F (60 °C) power circuit 10 A 140 °F (60 °C) control circuit
Irms rated making capacity	140 A 440 V AC control circuit IEC 60947-5-1 140 A AC control circuit IEC 60947-5-1 1000 A 440 V power circuit IEC 60947
Rated breaking capacity	1000 KA 440 V power circuit IEC 60947
[Icw] rated short-time withstand current	520 A 104 °F (40 °C) - 10 s power circuit 900 A 104 °F (40 °C) - 1 s power circuit
Associated fuse rating	125 A gG ≤ 690 V type 2 power circuit 160 A gG ≤ 690 V type 1 power circuit IEC 60947-5-1 125 A gG ≤ 690 V type 1 power circuit 10 A gG control circuit IEC 60947-5-1
Average impedance	1.5 Ohm - Ith 80 A 50 Hz power circuit

Power dissipation per pole	6.4 W AC-1 4.2 W AC-3e 6.3 W AC-3 9.6 W AC-1
[Ui] rated insulation voltage	Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL IEC 60947-1 Control circuit 690 V IEC 60947-1 Power circuit 690 V CSA IEC 60947-1 Control circuit 600 V CSA
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 KV IEC 60947
Safety reliability level	B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	6000000 Cycles
Control circuit type	AC 50/60 Hz
Coil technology	Without built-in
Control circuit voltage limits	0.8...1.1 Uc -40...140 °F (-40...60 °C) operational AC 50 Hz 0.85...1.1 Uc -40...140 °F (-40...60 °C) operational AC 60 Hz 1...1.1 Uc 140...158 °F (60...70 °C) operational AC 50/60 Hz 0.3...0.6 Uc -40...158 °F (-40...70 °C) drop-out AC 50/60 Hz
Inrush power in VA	160 VA 0.75 68 °F (20 °C)) 140 VA 0.75 68 °F (20 °C))
Hold-in power consumption in VA	15 VA 50 Hz 0.3 68 °F (20 °C)) 13 VA 60 Hz 0.3 68 °F (20 °C))
Heat dissipation	4...5 W 50/60 Hz control circuit
Operating time	12...26 ms closing 4...19 ms opening
Maximum operating rate	3600 Cyc/Mn 140 °F (60 °C)
Connections - terminals	Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) rigid without cable end Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) flexible without cable end Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) flexible without cable end Control circuit screw clamp terminals 1 0.00...0.00 in ² (1...2.5 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²) flexible with cable end Power circuit screw terminals 1 0.00...0.04 in ² (2.5...25 mm ²) rigid Power circuit screw terminals 2 0.00...0.02 in ² (2.5...16 mm ²) rigid without cable end Power circuit screw terminals 1 0.00...0.04 in ² (2.5...25 mm ²) flexible without cable end Power circuit screw terminals 2 0.00...0.02 in ² (2.5...16 mm ²) flexible without cable end Power circuit screw terminals 1 0.00...0.04 in ² (2.5...25 mm ²) flexible with cable end Power circuit screw terminals 2 0.00...0.02 in ² (2.5...10 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) rigid Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) rigid
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal Philips No 2 Power circuit 44.25 lbf.in (5 N.m) screw terminal flat Ø 6 to Ø 8 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal pozidriv No 2 Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal flat Ø 6 mm
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Mirror contact 1 NC IEC 60947-4-1 Mechanically linked 1 NO + 1 NC IEC 60947-5-1
Minimum switching voltage	17 V control circuit
Minimum switching current	5 MA control circuit
Insulation resistance	> 10 MOhm control circuit
Non-overlap time	1.5 Ms on energisation between NC and NO contacts 1.5 Ms on de-energisation between NC and NO contacts
Mounting Support	Plate Rail

Environment

Standards	EN 60947-4-1 CSA C22.2 No 14 IEC 60947-4-1 EN 60947-5-1 UL 508
Product Certifications	DNV UL RINA CCC CSA LROS (Lloyds register of shipping) BV GL UKCA UL
IP degree of protection	IP2x VDE 0106 IP2x IEC 60529
Protective treatment	TH 3)IEC 60068-2-30
Climatic withstand	IACS E10 exposure to damp heat
Operating altitude	0...9842.52 ft (0...3000 m)
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor closed 15 Gn for 11 ms) Vibrations contactor opened 2 Gn, 5...300 Hz) Vibrations contactor closed 4 Gn, 5...300 Hz) Shocks contactor opened 10 Gn for 11 ms)
Height	4.80 In (122 mm)
Width	2.76 In (70 mm)
Depth	4.65 In (118 mm)
Net Weight	4.82 Lb(US) (2.185 kg)
Quantity per Set	Set of 10

Ordering and shipping details

Category	22357-CTR, TESYS D, OPEN, 40-65A AC
Discount Schedule	I12
GTIN	3389110437836
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.74 In (9.5 cm)
Package 1 Width	5.20 In (13.2 cm)
Package 1 Length	5.51 In (14.0 cm)
Package 1 Weight	3.19 Lb(US) (1.446 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Height	5.91 In (15 cm)
Package 2 Width	11.81 In (30 cm)
Package 2 Length	15.75 In (40 cm)
Package 2 Weight	16.67 Lb(US) (7.561 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**