

# TeSys Deca reversing contactor - 3P(3 NO) - AC-3 - <= 440 V 18 A - 230 V AC coil

LC2D183P7

! Discontinued on: 10/10/2020

① Discontinued

#### Main

Range	TeSys	
product name	TeSys Deca	
Product or component type	Reversing contactor	
Device short name	LC2D	
Contactor application	Motor control Resistive load	
Utilisation category	AC-1 AC-3	
Device presentation	Preassembled with reversing power busbar	
Poles description	3P	
power pole contact composition	3 NO	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	
[le] rated operational current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 18 A (at <60 °C) at <= 440 V AC AC-3 for power circuit	
Motor power kW	4 kW at 220230 V AC 50 Hz 7.5 kW at 380400 V AC 50 Hz 9 kW at 415440 V AC 50 Hz 10 kW at 500 V AC 50 Hz 10 kW at 660690 V AC 50 Hz	
motor power HP (UL / CSA)	1 hp at 115 V AC 60 Hz for 1 phase motors 3 hp at 230/240 V AC 60 Hz for 1 phase motors 5 hp at 200/208 V AC 60 Hz for 3 phases motors 5 hp at 230/240 V AC 60 Hz for 3 phases motors 10 hp at 460/480 V AC 60 Hz for 3 phases motors 15 hp at 575/600 V AC 60 Hz for 3 phases motors	
Control circuit type	AC at 50/60 Hz	
[Uc] control circuit voltage	230 V AC 50/60 Hz	
Auxiliary contact composition	1 NO + 1 NC	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947	
Overvoltage category	III	
[Ith] conventional free air thermal current	10 A (at 60 °C) for signalling circuit 25 A (at 60 °C) for power circuit	
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 300 A at 440 V for power circuit conforming to IEC 60947	
Rated breaking capacity	300 A at 440 V for power circuit conforming to IEC 60947	

[Icw] rated short-time withstand current	40 A 40 °C - 10 min for power circuit 84 A 40 °C - 1 min for power circuit 145 A 40 °C - 10 s for power circuit 240 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 50 A gG at <= 690 V coordination type 1 for power circuit 35 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit	
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
Electrical durability	1.65 Mcycles 18 A AC-3 at Ue <= 440 V 1 Mcycles 32 A AC-1 at Ue <= 440 V	
Power dissipation per pole	0.8 W AC-3 2.5 W AC-1	
Front cover	With	
Interlocking type	Mechanical	
Mounting support	Plate Rail	
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508	
Product certifications	BV CCC RINA GOST LROS (Lloyds register of shipping) DNV GL UL CSA	
Connections - terminals	Control circuit: spring terminals 1 cable(s) 2.5 mm²flexible without cable end Control circuit: spring terminals 2 cable(s) 2.5 mm²flexible without cable end Power circuit: spring terminals 1 cable(s) 4 mm²flexible without cable end Power circuit: spring terminals 2 cable(s) 4 mm²flexible without cable end	
Operating time	1222 ms closing 419 ms opening	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Mechanical durability	15 Mcycles	
Maximum operating rate	3600 cyc/h 60 °C	
Complementary		
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz	
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C)	

Hold-in power consumption in VA	7A 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	23 W at 50/60 Hz	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching current	5 mA for signalling circuit	
Minimum switching voltage	17 V for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Insulation resistance	> 10 MOhm for signalling circuit	

### **Environment**

IP degree of protection	IP20 front face conforming to IEC 60529	
Climatic withstand	conforming to IACS E10 conforming to IEC 60947-1 Annex Q category D	
Protective treatment	TH conforming to IEC 60068-2-30	
pollution degree	3	
Ambient air temperature for operation	-4060 °C 6070 °C with derating	
Ambient air temperature for storage	-6080 °C	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 4 Gn, 5300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms	
Height	99 mm	
Width	90 mm	
Depth	92 mm	
Net weight	0.707 kg	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.9 cm
Package 1 Width	11.4 cm
Package 1 Length	11 cm
Package 1 Weight	730 g

## **Contractual warranty**

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

#### **Use Better**

EU RoHS Directive	Compliant
PVC free	Yes
Use Again	
○ Repack and remanufacture	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins