

## Thyristor/Diode Modules M## 431

### Absolute Maximum Ratings

$V_{RRM}$ $V_{DRM}$ [V]	MCC	MCA	MCK	MCD	MDC
2000	431-20io2	431-20io2	431-20io2	431-20io2	431-20io2
2200	431-22io2	431-22io2	431-22io2	431-22io2	431-22io2
2400	431-24io2	431-24io2	431-24io2	431-24io2	431-24io2

	VOLTAGE RATINGS	MAXIMUM LIMITS	UNITS
$V_{DRM}$	Repetitive peak off-state voltage <sup>1)</sup>	2000-2400	V
$V_{DSM}$	Non-repetitive peak off-state voltage <sup>1)</sup>	2100-2500	V
$V_{RRM}$	Repetitive peak reverse voltage <sup>1)</sup>	2000-2400	V
$V_{RSM}$	Non-repetitive peak reverse voltage <sup>1)</sup>	2100-2500	V

	OTHER RATINGS	MAXIMUM LIMITS	UNITS
$I_{T(AV)M}$	Maximum average on-state current, $T_C = 85^\circ\text{C}$ <sup>2)</sup>	429	A
$I_{T(AV)M}$	Maximum average on-state current, $T_C = 100^\circ\text{C}$ <sup>2)</sup>	296	A
$I_{T(RMS)M}$	Nominal RMS on-state current, $T_C = 55^\circ\text{C}$ <sup>2)</sup>	1020	A
$I_{T(\text{d.c.})}$	D.C. on-state current, $T_C = 55^\circ\text{C}$	809	A
$I_{TSM}$	Peak non-repetitive surge $t_p = 10 \text{ ms}$ , $V_{RM} = 60\% V_{RRM}$ <sup>3)</sup>	10.9	kA
$I_{TSM2}$	Peak non-repetitive surge $t_p = 10 \text{ ms}$ , $V_{RM} \leq 10 \text{ V}$ <sup>3)</sup>	12.0	kA
$I^2t$	$I^2t$ capacity for fusing $t_p = 10 \text{ ms}$ , $V_{RM} = 60\% V_{RRM}$ <sup>3)</sup>	$594 \times 10^3$	$\text{A}^2\text{s}$
$I^2t$	$I^2t$ capacity for fusing $t_p = 10 \text{ ms}$ , $V_{RM} \leq 10 \text{ V}$ <sup>3)</sup>	$720 \times 10^3$	$\text{A}^2\text{s}$
$(di/dt)_{cr}$	Critical rate of rise of on-state current (repetitive) <sup>4)</sup>	200	$\text{A}/\mu\text{s}$
	Critical rate of rise of on-state current (non-repetitive) <sup>4)</sup>	400	$\text{A}/\mu\text{s}$
$V_{RGM}$	Peak reverse gate voltage	5	V
$P_{G(AV)}$	Mean forward gate power	4	W
$P_{GM}$	Peak forward gate power	30	W
$V_{ISOL}$	Isolation Voltage <sup>5)</sup>	3000	V
$T_{vj\ op}$	Operating temperature range	-40 to +125	$^\circ\text{C}$
$T_{stg}$	Storage temperature range	-40 to +125	$^\circ\text{C}$

#### Notes:

- 1) De-rating factor of 0.13% per  $^\circ\text{C}$  is applicable for  $T_{vj}$  below  $25^\circ\text{C}$ .
- 2) Single phase; 50 Hz,  $180^\circ$  half-sinewave.
- 3) Half-sinewave,  $125^\circ\text{C}$   $T_{vj}$  initial.
- 4)  $V_D = 67\% V_{DRM}$ ,  $I_{FG} = 2 \text{ A}$ ,  $t_f \leq 0.5\mu\text{s}$ ,  $T_C = 125^\circ\text{C}$ .
- 5) AC RMS voltage, 50 Hz, 1min test

Characteristics

	PARAMETER	MIN.	TYP.	MAX.	TEST CONDITIONS <sup>1)</sup>	UNITS
$V_{TM}$	Maximum peak on-state voltage	-	1.30	1.50	$I_{TM} = 1256 \text{ A}$	V
$V_{TO}$	Threshold voltage	-	-	1.00		V
$r_T$	Slope resistance	-	-	0.41		$\text{m}\Omega$
$(dv/dt)_{cr}$	Critical rate of rise of off-state voltage	1000	-	-	$V_D = 80\% V_{DRM}$ , linear ramp, Gate o/c	$\text{V}/\mu\text{s}$
$I_{DRM}$	Peak off-state current	-	-	100	Rated $V_{DRM}$	mA
$I_{RRM}$	Peak reverse current	-	-	100	Rated $V_{RRM}$	mA
$V_{GT}$	Gate trigger voltage	-	-	2.5		V
$I_{GT}$	Gate trigger current	-	-	250	$T_{vj} = 25^\circ\text{C}$ , $V_D = 12 \text{ V}$ , $I_T = 3 \text{ A}$	mA
$V_{GD}$	Gate non-trigger voltage	0.25	-	-	67% $V_{DRM}$	V
$I_L$	Latching current	-	-	1000	$V_D = 12 \text{ V}$ , $T_{vj} = 25^\circ\text{C}$	mA
$I_H$	Holding current	-	-	300	$V_D = 12 \text{ V}$ , $T_{vj} = 25^\circ\text{C}$	mA
$t_{gd}$	Gate controlled turn-on delay time	-	-	2.5		
$t_{gt}$	Turn-on time	-	-	8.0	$I_{FG} = 2 \text{ A}$ , $t_r = 1 \mu\text{s}$ , $V_D = 40\% V_{DRM}$ , $I_{TM} = 1500 \text{ A}$ , $di/dt = 10 \text{ A}/\mu\text{s}$ , $T_{vj} = 25^\circ\text{C}$	$\mu\text{s}$
$Q_{rr}$	Recovered Charge	-	1600	1800		$\mu\text{C}$
$Q_{ra}$	Recovered Charge, 50% chord	-	1350	-	$I_{TM} = 800 \text{ A}$ , $t_p = 1 \text{ ms}$ , $di/dt = 10 \text{ A}/\mu\text{s}$ ,	$\mu\text{C}$
$I_{rm}$	Reverse recovery current	-	120	-	$V_R = 100 \text{ V}$	A
$t_{rr}$	Reverse recovery time, 50% chord	-	23	-		$\mu\text{s}$
$t_q$	Turn-off time	-	-	250	$I_{TM} = 1500 \text{ A}$ , $t_p = 1 \text{ ms}$ , $di/dt = 10 \text{ A}/\mu\text{s}$ , $V_R = 100 \text{ V}$ , $V_{DR} = 67\% V_{DRM}$ , $dv_{DR}/dt = 50 \text{ V}/\mu\text{s}$	$\mu\text{s}$
$R_{thJC}$	Thermal resistance, junction to case	-	-	0.062	Single Thyristor	K/W
		-	-	0.031	Whole Module	K/W
$R_{thCH}$	Thermal resistance, case to heatsink	-	-	0.02	Single Thyristor	K/W
		-	-	0.01	Whole Module	K/W
$F_1$	Mounting force (to heatsink)	5.1	-	6.9		Nm
$F_2$	Mounting force (to terminals)	10.8	-	13.2	<sup>2)</sup>	Nm
$W_t$	Weight	-	1.5	-		kg

**Notes:**

- 1) Unless otherwise indicated  $T_{vj}=125^\circ\text{C}$ .  
 2) Screws must be lubricated.

## Notes on Ratings and Characteristics

### 1.0 Voltage Grade Table

Voltage Grade	$V_{DRM}$ V	$V_{RRM}$ V	$V_{DSM}$ V	$V_{RSM}$ V	$V_D$ DC V	$V_R$ DC V
20	2000		2100		1500	
22	2200		2300		1650	
24	2400		2500		1800	

### 2.0 Extension of Voltage Grades

This report is applicable to other voltage grades when supply has been agreed by Sales/Production.

### 3.0 De-rating Factor

A blocking voltage de-rating factor of 0.13%/°C is applicable to this device for  $T_{vj}$  below 25°C.

### 4.0 Repetitive dv/dt

Standard dv/dt is 1000V/μs.

### 5.0 Snubber Components


When selecting snubber components, care must be taken not to use excessively large values of snubber capacitor or excessively small values of snubber resistor. Such excessive component values may lead to device damage due to the large resultant values of snubber discharge current. If required, please consult the factory for assistance.

### 6.0 Rate of rise of on-state current

The maximum un-primed rate of rise of on-state current must not exceed 400A/μs at any time during turn-on on a non-repetitive basis. For repetitive performance, the on-state rate of rise of current must not exceed 200A/μs at any time during turn-on. Note that these values of rate of rise of current apply to the total device current including that from any local snubber network.

### 7.0 Gate Drive

The nominal requirement for a typical gate drive is illustrated below. An open circuit voltage of at least 30V is assumed. This gate drive must be applied when using the full di/dt capability of the device.



The magnitude of  $I_{GM}$  should be between five and ten times  $I_{GT}$ , which is shown on page 2. Its duration ( $t_{p1}$ ) should be 20μs or sufficient to allow the anode current to reach ten times  $I_L$ , whichever is greater. Otherwise, an increase in pulse current could be needed to supply the necessary charge to trigger. The 'back-porch' current  $I_G$  should remain flowing for the same duration as the anode current and have a magnitude in the order of 1.5 times  $I_{GT}$ .

## 8.0 Computer Modelling Parameters

### 8.1 Thyristor Dissipation Calculations

$$I_{AV} = \frac{-V_{T0} + \sqrt{V_{T0}^2 + 4 \cdot ff^2 \cdot r_T \cdot W_{AV}}}{2 \cdot ff^2 \cdot r_T}$$

and:

$$W_{AV} = \frac{\Delta T}{R_{th}}$$

$$\Delta T = T_{j\max} - T_K$$

Where  $V_{T0} = 1.0$  V,  $r_T = 0.41$  mΩ.

$R_{th}$  = Supplementary thermal impedance, see table below and

$ff$  = Form factor, see table below.

Supplementary Thermal Impedance							
Conduction Angle	30°	60°	90°	120°	180°	270°	d.c.
Square wave	0.0702	0.0685	0.0679	0.0668	0.0658	0.0637	0.0620
Sine wave	0.0677	0.0673	0.0664	0.0655	0.0650		

Form Factors							
Conduction Angle	30°	60°	90°	120°	180°	270°	d.c.
Square wave	3.464	2.449	2	1.732	1.414	1.149	1
Sine wave	3.98	2.778	2.22	1.879	1.57		

### 8.2 Calculating thyristor $V_T$ using ABCD Coefficients

The on-state characteristic  $I_T$  vs.  $V_T$ , on page 6 is represented by a set of constants A, B, C, D, forming the coefficients of the representative equation for  $V_T$  in terms of  $I_T$  given below:

$$V_T = A + B \cdot \ln(I_T) + C \cdot I_T + D \cdot \sqrt{I_T}$$

The constants, derived by curve fitting software, are given below for both hot and cold characteristics. The resulting values for  $V_T$  agree with the true device characteristic over a current range, which is limited to that plotted.

25°C Coefficients		125°C Coefficients	
A	1.001105	A	0.6018822
B	0.1016930	B	0.06092552
C	4.732084E <sup>-4</sup>	C	2.507715E <sup>-4</sup>
D	-0.02366814	D	4.119984E <sup>-3</sup>

### 8.3 D.C. Thermal Impedance Calculation

$$r_t = \sum_{p=1}^{p=n} r_p \cdot \left( 1 - e^{\frac{-t}{\tau_p}} \right)$$

Where  $p = 1$  to  $n$  and:

- $n$  = number of terms in the series
- $t$  = Duration of heating pulse in seconds
- $r_t$  = Thermal resistance at time  $t$
- $r_p$  = Amplitude of  $p_{th}$  term
- $\tau_p$  = Time Constant of  $r_{th}$  term

The coefficients for this device are shown in the table below:

D.C.					
Term	1	2	3	4	5
$r_p$	$1.37 \times 10^{-3}$	$4.86 \times 10^{-3}$	0.0114	0.0223	0.0221
$\tau_p$	$7.6 \times 10^{-4}$	$8.6 \times 10^{-3}$	0.101	0.56	3.12

### 9.0 Reverse recovery ratings

- (i)  $Q_{ra}$  is based on 50%  $I_{RM}$  chord as shown in Fig. 1




Fig. 1

- (ii)  $Q_{rr}$  is based on a 150  $\mu s$  integration time i.e.

$$Q_{rr} = \int_0^{150 \mu s} i_{rr} dt$$

(iii)

$$K \text{ Factor} = \frac{t_1}{t_2}$$

Curves

Figure 1 – On-state characteristics of Limit device




Figure 2 – Gate characteristics – Trigger limits




Figure 3 – Gate characteristics – Power curves








Figure 4 - Total recovered charge,  $Q_{rr}$ Figure 5 - Recovered charge,  $Q_{ra}$  (50% chord)Figure 6 - Peak reverse recovery current,  $I_{rm}$ Figure 7 - Maximum recovery time,  $t_{rr}$  (50% chord)

Figure 8 – On-state current vs. Power dissipation  
– Sine wave




Figure 9 – On-state current vs. Heatsink temperature – Sine wave




Figure 10 – On-state current vs. Power dissipation – Square wave




Figure 11 – On-state current vs. Heatsink temperature – Square wave







Figure 12 – Maximum surge and  $I^2t$  Ratings

Figure 13 – Transient thermal impedance



## Outline Drawing &amp; Ordering Information



## ORDERING INFORMATION

(Please quote 11 digit code as below)

M	##	431	♦♦	io	2
Fixed Type Code	Configuration code CC, CA, CK, CD or DC	Fixed Type Code	Voltage code V <sub>RRM</sub> /100 20-24	i = Critical dv/dt 1000 V/μs o = Typical turn-off time	Fixed Version Code

Typical order code: MCD431-22io2 - MCD configuration, 2200V V<sub>RRM</sub>

**IXYS Semiconductor GmbH**  
 Edisonstraße 15  
 D-68623 Lampertheim  
 Tel: +49 6206 503-0  
 Fax: +49 6206 503-627  
 E-mail: [marcom@ixys.de](mailto:marcom@ixys.de)



**Westcode Semiconductors Ltd**  
 Langley Park Way, Langley Park,  
 Chippenham, Wiltshire, SN15 1GE.  
 Tel: +44 (0)1249 444524  
 Fax: +44 (0)1249 659448  
 E-mail: [WSL\\_sales@westcode.com](mailto:WSL_sales@westcode.com)

**IXYS Corporation**  
 1590 Buckeye Drive  
 Milpitas CA 95035 7418 USA  
 Tel: +1 (408) 547 9000  
 Fax: +1 (408) 496 0670  
 E-mail: [sales@ixys.net](mailto:sales@ixys.net)

**WESTCODE**  
 An IXYS Company

[www.westcode.com](http://www.westcode.com)

**IXYS Long Beach, Inc**  
 2500 Mira Mar Ave, Long Beach  
 CA 90815 USA  
 Tel: +1 (562) 296 6584  
 Fax: +1 (562) 296 6585  
 E-mail: [service@ixyslongbeach.com](mailto:service@ixyslongbeach.com)

The information contained herein is confidential and is protected by Copyright. The information may not be used or disclosed except with the written permission of and in the manner permitted by the proprietors IXYS Semiconductors GmbH.  
 In the interest of product improvement, IXYS reserves the right to change specifications at any time without prior notice.

© IXYS Semiconductor GmbH.