



FEATURES

1. Slim size (width 5 mm .197 inch, height 12.5 mm .492 inch) permits higher density mounting

Despite the slim 5 mm width, the 20 mm length is still compact and the 12.5 mm profile is low. Even when a socket is used, the height is still only 18 mm. Suitable for high-density mounting, these relays enable device size smaller.

2. Nominal operating power: High sensitivity of 120mW

Enables smaller power supplies, facilitates energy saving applications, and contributes to device size smaller.

3. Control from low level loads to 5 A

Use of gold-clad twin contacts enables control of low level loads down to 100 μ A and up to 5 A 250 V AC and 30 V DC.

4. Reinforced according to IEC1131-2 (TÜV)

PAD type: 3.1 mm clearance
3.6 mm creepage distance

5. High surge breakdown voltage (4000 V) and high breakdown voltage (2000 V)

Between contacts and coil of 2,000 V and surge resistance of 4,000 V work to prevent controller malfunctions caused by noise and surges.

6. Outstanding vibration and shock resistance.

Functional shock resistance: 147 m/s²
Functional vibration resistance:
10 to 55 Hz (at double amplitude of 2.5 mm .098 inch)

Keeps equipment from miss-operation due to vibration and shock.

Can be used as mounted on control panel doors.

7. Sealed construction allows automatic washing.

8. SIL (single in line) terminal layout

9. Complies with safety standards

Complies with Japanese Electrical Appliance and Material Safety Law, and certified by UL, CSA, and TÜV.

10. Sockets are also available

TYPICAL APPLICATIONS

1. Industrial equipment, office equipment
2. Measuring devices and test equipment
3. Interface relays for programmable controllers
4. Output relays in small devices such as timers, counters, sensors, and temperature controllers.

ORDERING INFORMATION

PA(D) 1a -

Contact arrangement
1a: 1 Form A (Bifurcated)

Coil voltage (DC)
5, 6, 9, 12, 18, 24V

Notes: 1) The PAD type offers slightly higher clearance (3.1 mm) and creepage distance (3.6 mm).
2) UL/CSA, TÜV approved type is standard.

TYPES

Contact arrangement	Nominal coil voltage	Part No.
1 Form A	5V DC	PA(D)1a-5V
	6V DC	PA1a-6V
	9V DC	PA1a-9V
	12V DC	PA(D)1a-12V
	18V DC	PA(D)1a-18V
	24V DC	PA(D)1a-24V

Standard packing: Carton: 25 pcs.; Case: 1,000 pcs.

RATING

1. Coil data

Nominal coil voltage	Pick-up voltage (at 20°C 68°F)	Drop-out voltage (at 20°C 68°F)	Nominal operating current [$\pm 10\%$] (at 20°C 68°F)	Coil resistance [$\pm 10\%$] (at 20°C 68°F)	Nominal operating power	Max. allowable voltage (at 20°C 68°F)
5V DC	70%V or less of nominal voltage ** (Initial)	5%V or more of nominal voltage** (Initial)	24mA	208 Ω	120mW	120%V of nominal voltage
6V DC			20mA	300 Ω		
9V DC			13.3mA	675 Ω		
12V DC			10mA	1,200 Ω		
18V DC			6.7mA	2,700 Ω		
24V DC			7.5mA	3,200 Ω		

Notes:*1Pulse drive (JIS C 5442)

**2 24V DC, 120mW type are also available, please consult us.

2. Specifications


Characteristics	Item	Specifications	
Contact	Arrangement	1 Form A	
	Initial contact resistance, max.	Max. 30 mΩ (By voltage drop 6 V DC 1A)	
	Contact material	Au-clad AgNi type	
Rating	Nominal switching capacity (resistive load)	5 A 250 V AC, 5 A 30 V DC	
	Max. switching power (resistive load)	1,250 VA, 150 W	
	Max. switching voltage	250 V (AC), 110 V (DC)	
	Max. switching current	5 A	
	Nominal operating power	120 mW (5 to 18 V DC), 180 mW (24 V DC)	
	Min. switching capacity (Reference value)*1	100μA 100mV DC	
Electrical characteristics	Insulation resistance (Initial)	Min. 1,000MΩ (at 500V DC) Measurement at same location as "Initial breakdown voltage" section.	
	Breakdown voltage (Initial)	Between open contacts	1,000 Vrms for 1min. (Detection current: 10mA.)
		Between contact and coil	2,000 Vrms for 1min. (Detection current: 10mA.)
	Surge breakdown voltage (Initial)	Between contacts and coil ²	4,000 V
	Temperature rise (at 20°C 68°F)		Max. 45°C (By resistive method, nominal voltage applied to the coil, nominal switching capacity.)
	Operate time (at nominal voltage) (at 20°C 68°F)		Max. 10 ms
	Release time (at nominal voltage) (at 20°C 68°F)		Max. 5 ms
Mechanical characteristics	Shock resistance	Functional	Min. 147 m/s ² (Half-wave pulse of sine wave: 11 ms; detection time: 10μs.)
		Destructive	Min. 980 m/s ² (Half-wave pulse of sine wave: 6 ms.)
	Vibration resistance	Functional	10 to 55 Hz at double amplitude of 2.5 mm (Detection time: 10μs.)
		Destructive	10 to 55 Hz at double amplitude of 3.5 mm
Expected life	Mechanical	Min. 2×10 ⁷ (at 180 cpm)	
	Electrical	Min. 10 ⁵ (3 A 250 V AC, 30 V DC, resistive load) Min. 5×10 ⁴ (5 A 250 V AC, 30 V DC, resistive load) (at 20 cpm)	
Conditions	Conditions for operation, transport and storage ³	Ambient temperature: -40°C to 70°C -40°F to 158°F; Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature)	
	Max. operating speed (at rated load)	20 cpm	
Unit weight		Approx. 3 g .15 oz	

Notes:


- *1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load.
- *2 Wave is standard shock voltage of ±1.2×50μs according to JEC-212-1981.
- *3 Refer to "6. Usage, Storage and Transport Conditions" in [AMBIENT ENVIRONMENT section in Relay Technical Information](#).

REFERENCE DATA

1. Max. switching capacity




2. Life curve




3.-(1) Coil temperature rise (120 mW)

Tested sample: PA1a-12V
Measured portion: Inside the coil
Ambient temperature: 20°C 68°F




3.-(2) Coil temperature rise (180 mW)

Tested sample: PA1a-24V
 Measured portion: Inside the coil
 Ambient temperature: 20°C 68°F




Tested sample: PA1a-12V, 20 pcs.




4.-(2) Operate & release time (180 mW)

Tested sample: PA1a-24V, 20 pcs.




5. Ambient temperature characteristics

Tested sample: PA1a-12V, 6 pcs.




6. Malfunctional shock

Tested sample: PA1a-12V, 6 pcs.




DIMENSIONS (Unit: mm inch)

Relay




General tolerance: $\pm 0.3 \pm .012$

PC board pattern (Bottom view)



Tolerance: $\pm 0.1 \pm .004$

Schematic (Bottom view)




PA Socket




PA1a-PS

1. Standard type (PA1a-PS)
External dimensions




General tolerance: $\pm 0.3 \pm .012$

PC board pattern (Bottom view)
PA1a-PS




Tolerance: $\pm 0.1 \pm .004$

2. Self clinching type (PA1a-PS-H)
External dimensions



General tolerance: $\pm 0.3 \pm .012$


PC board pattern (Bottom view)
PA1a-PS-H



Tolerance: $\pm 0.1 \pm .004$


NOTES

1. If it includes ripple, the ripple factor should be less than 5%.
2. Specification values for pick-up and drop-out voltages are for the relay mounting with its terminals below.




3. When mounting the relays within 1 mm (.039 inch), please notice the condition below.

1) Mount the relays in the same direction.





2) Coil terminals (Terminal No. 1 & 2) polarity should be arranged in the same direction.



3) Allowable contact current is 2 A.

- 4) About the electrical life for close mounting, please refer to data below.



For Cautions for Use, see [Relay Technical Information](#).