

# Wires Accessories

## Cable Glands




- Material: Brass with nickel plated
- Clamp piece: PA
- Seal piece: NBR & EPDM
- Protection class to: IP68 (tighten part)
- Temperature range: -40°C to 100°C, short time to 120°C

### PG series metal cable glands - breakproof

| Thread | Ømm   | GL mm | H mm | h mm | W mm | AG mm | Order NO.  |
|--------|-------|-------|------|------|------|-------|------------|
| PG7    | 3-6.5 | 10    | 55   | 6.8  | 14   | 12.5  | T.P071006F |
| PG7    | 2-5   | 10    | 55   | 6.8  | 14   | 12.5  | T.P071005F |
| PG9    | 4-8   | 10    | 66   | 8.2  | 17   | 15.2  | T.P091008F |
| PG9    | 2-9   | 10    | 66   | 8.2  | 17   | 15.2  | T.P091006F |
| PG11   | 5-10  | 10    | 77   | 10.3 | 20   | 18.6  | T.P111010F |
| PG11   | 3-7   | 10    | 77   | 10.3 | 20   | 18.6  | T.P111007F |
| PG13.5 | 6-12  | 10    | 88   | 12.3 | 22   | 20.4  | T.P131012F |
| PG13.5 | 5-9   | 10    | 88   | 12.3 | 22   | 20.4  | T.P131009F |
| PG16   | 10-14 | 10    | 98   | 14.3 | 24   | 22.5  | T.P161014F |
| PG16   | 7-12  | 10    | 98   | 14.3 | 24   | 22.5  | T.P161012F |
| PG21   | 13-18 | 12    | 111  | 18.4 | 30   | 28.3  | T.P211218F |
| PG21   | 9-16  | 12    | 111  | 18.4 | 30   | 28.3  | T.P211216F |


### Dimension



### PG series round stopple

| Thread | GLmm | Hmm | Dmm | AGmm | Order NO. |
|--------|------|-----|-----|------|-----------|
| PG7    | 5    | 8   | 14  | 12.5 | T.P071    |
| PG9    | 6    | 9   | 17  | 15.2 | T.P091    |
| PG11   | 6    | 9   | 20  | 18.6 | T.P111    |
| PG13.5 | 6.5  | 9.5 | 22  | 20.4 | T.P131    |
| PG16   | 6.5  | 9.5 | 24  | 22.5 | T.P161    |
| PG21   | 7    | 11  | 30  | 28.3 | T.P211    |
| PG29   | 8    | 12  | 39  | 37   | T.P291    |
| PG36   | 9    | 15  | 50  | 47   | T.P361    |
| PG42   | 10   | 16  | 57  | 54   | T.P421    |
| PG48   | 10   | 16  | 64  | 59.3 | T.P481    |

### Dimension



- Material: Brass with nickel plated
- Seal piece: NBR & EPDM
- Protection class to: IP65
- Temperature range: -40°C to 100°C