Specifications



① To be discontinued

Central I/O module, SpaceLogic, 8 universal inputs, 4 analog voltage outputs [TAA]

SXWUI8V4X10001

Discontinued on: Dec 31, 2024

Product availability: Stock - Normally stocked in distribution facility

Main

| Flame Retardance | UL94V0-5VB | |
|--|--|--|
| Width | 3.5 in (90 mm) | |
| Product Certifications | ICES-003 FCC part 15 class B CE RCM UL | |
| Product Weight | 5.4 oz (152 g) | |
| Product or Component Type | I/O module | |
| Device short name | UI-8/AO-V-4 | |
| Height | 4.5 in (114 mm) | |
| Ambient Air Temperature for Storage | -4158 °F (-2070 °C) | |
| Depth | 2.5 in (64 mm) | |
| Ambient air temperature for operation | 32122 °F (050 °C) | |
| IP Degree of Protection | IP20 | |
| Power Consumption in W | 1 W | |
| Input/Output Type | universal input | |
| Relative Humidity | 095 % non-condensing | |
| Number of Outputs | 4 analog output | |
| [Us] Rated Supply Voltage | 24 V DC | |
| product name | I/O Modules | |
| Product brand | Schneider Electric | |
| Range | EcoStruxure Building Operation | |

Complementary

| - | |
|-----------------------|------------------|
| Switching frequency | 25 Hz |
| Discrete input number | 8 |
| Mounting Support | DIN rail Wall |
| Electrical Connection | Plug-in sub-base |
| Control Type | Without |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Product Compatibility | Continuum Johnson Control Balco I/NET Xenta Satchwell Honeywell | |
|-----------------------|---|--|
| Analogue input type | Configurable voltage, current or probe 020 mA Configurable voltage, current or probe 010 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes | |
| Local signalling | LED green/red) high signal level LED green/red) low signal level | |
| Range compatibility | EcoStruxure Building Operation TB-IO-W1 terminal base | |
| Standards | UL 864 UL 916 FCC CFR47 part 15 | |
| Material | ABS + PC | |

Ordering and shipping details

| Category | US1BMS180230 | |
|-------------------|---------------|--|
| Discount Schedule | BMS1 | |
| GTIN | 3606480610653 | |
| Returnability | Yes | |
| Country of origin | US | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|-------------------------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 2.24 in (5.700 cm) | |
| Package 1 Width | 3.58 in (9.100 cm) | |
| Package 1 Length | 4.61 in (11.700 cm) | |
| Package 1 Weight | 5.820 oz (165.000 g) | |
| Unit Type of Package 2 | S02 | |
| Number of Units in Package 2 | 18 | |
| Package 2 Height | 5.91 in (15.000 cm) | |
| Package 2 Width | 11.81 in (30.000 cm) | |
| Package 2 Length | 15.75 in (40.000 cm) | |
| Package 2 Weight | 7.551 lb(US) (3.425 kg) | |

Compliance

Compliance

TAA

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

| $\ensuremath{ arphi }$ Environmental footprint | |
|--|----|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 42 |

Use Better

| Packaging made with recycled cardboard | No |
|--|--|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 08bd611f-8419-43db-ad4e-34d847346717 |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| Halogen content performance | Halogen free plastic parts and cables product |
| PVC free | Yes |

Use Again

| ${\mathbb O}$ Repack and remanufacture | |
|--|--|
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |