

Light block for head 22mm, Harmony XB4, green, integral LED, 230...240V AC

ZBVM3

! Discontinued on: Jun 15, 2023 AD

! Discontinued

Main

Range of product	Harmony XB5 Harmony XB4 Light block	
Product or component type		
Device short name	ZBV	
Sale per indivisible quantity	5	
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN 60947-1 Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to EN 60947-1	
Signalling type	Steady	
Light source	Protected LED	
Bulb base	Integral LED	
Light block supply	Direct	
Light source colour	Green	
[Us] rated supply voltage	230240 V AC at 50/60 Hz	

Complementary

Net weight	0.017 kg	
Tightening torque	0.81.2 N.m conforming to EN 60947-1	
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver	
Supply voltage limits	195264 V AC	
Current consumption	14 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PF1	

Device presentation	Basic element	
Environment		
Protective treatment	тн	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
IP degree of protection	IP20 conforming to IEC 60529	
Standards	EN/IEC 60947-1 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-5-5 JIS C8201-5-1 JIS C8201-1	
Product certifications	CSA UL listed	
Resistance to fast transients	2 kV conforming to IEC 61000-4-4	
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3	
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2	
Electromagnetic emission	Class B conforming to IEC 55011	
[Us] rated supply voltage	230240 V	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.000 cm	
Package 1 Width	3.500 cm	
Package 1 Length	4.500 cm	
Package 1 Weight	9.000 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	5	
Package 2 Height	4.500 cm	
Package 2 Width	5.500 cm	
Package 2 Length	5.500 cm	
	3.300 dii	
Package 2 Weight	52.000 g	
Package 2 Weight Unit Type of Package 3		
	52.000 g	
Unit Type of Package 3	52.000 g \$03	
Unit Type of Package 3 Number of Units in Package 3	52.000 g S03 800	
Unit Type of Package 3 Number of Units in Package 3 Package 3 Height	52.000 g S03 800 30.000 cm	

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

Use Again


○ Repack and remanufacture	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

ZBVM3


Dimensions Drawings

Dimensions

with ZB5AZ009 Fixing Collar




with ZB4BZ009 Fixing Collar




Technical Illustration

Dimensions



+ ZB4BZ009



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB4

