



Main

| | |
|----------------------------|--|
| Range of product | OsiSense XC |
| Series name | Special format |
| Product or component type | Limit switch head |
| Device short name | ZC2J |
| Head type | Plunger head |
| Product compatibility | XC2J |
| Associated body | ZC2JD1 ZC2JC28 ZC2JD2 ZC2JC1 ZC2JC18 ZC2JC2 |
| Movement of operating head | Linear |
| Type of operator | Side plunger spring return metal |
| Type of approach | Lateral approach, 1 direction |

Complementary

| | |
|------------------|---------|
| Switch actuation | On end |
| Positive opening | Without |
| Net weight | 0.24 kg |
| Head material | Metal |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 246 g |
| Package 2 Weight | 3.647 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|