

Product data sheet

Characteristics

ZCKE655

limit switch head ZCKE - side steel roller
plunger vertical - +120 °C



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD39H29 ZCKJ5 ZCKJ5H7 ZCKJ2 ZCKJD39H7 ZCKJD37H29 ZCKJ1 ZCKJ2H29 ZCKJ8H7 ZCKJD31 ZCKJ6H7 ZCKJ21H29 ZCKJ9 ZCKJ1H29 ZCKJ5H29 ZCKJ9H7 ZCKJ7H29 ZCKJ6 ZCKJ11H7 ZCKJ11 ZCKJD31H29 ZCKJ6H29 ZCKJ2H7 ZCKJ21 ZCKJ7H7 ZCKJ8H29 ZCKJD35H29 ZCKJ21H7 ZCKJD37H7 ZCKJ1H7 ZCKJD31H7 ZCKJ9H29 ZCKJD35H7 ZCKJ11H29 ZCKJ8 ZCKJD39 ZCKJD35 ZCKJD37 ZCKJ7
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with vertical roller)
Type of approach	Vertical approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.205 kg
Head material	Metal

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

Packing Units

Package 1 Weight	304 g
------------------	-------

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------